VCXO VG7050CDN

SEIKO EPSON CORPORATION

Product name VG7050CDN 122.880000MHz CJHHBA
Product code / Ordering code X1G0048610011xx
Please refer to the 8.Packing information about xx (last 2 digits)

Output waveform CMOS
Complies with EU RoHS directive
Reference weight Typ.169mg


1.Absolute maximum ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Remarks
Maximum supply voltage	Vcc-GND	-0.3	-	+5	V	-
Storage temperature	T_stg	-55	-	+125	ºC	Storage as single product after unpacking.
Input voltage	Vin	-0.3	-	Vcc+0.3	V	Vc traminal

2.Specifications(characteristics)


Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Remarks
Output frequency	f0		122.8800		MHz	
Supply voltage	Vcc	3.135	3.3	3.465	V	-
Control voltage	Vc	0	1.65	3.3	V	Vc=1.65V+/-1.65V
Operating temperature	T_use	-40	-	+105	ºC	-
Frequency tolerance	f_tol	-50	-	+50	$x10^{-6}$	T_Use
Current consumption	Icc	-	-	30	mA	-
Disable current	I_dis	-	-	-	mA	OE=GND
Frequency control range	f_cont	+/-100	-	-	$x10^{-6}$	-
Absolute pull range	APR	+/-50	-	-	$x10^{-6}$	-
Modulation characteristics	BW	10	-	-	kHz	+/-3dB
Input resistance	Rin	10	-	-	MΩ	Vc terminal
Linearity	F_{LIN}	-	-	+/-10	%	-
Frequency change polarity	-		Positive		–	-
Symmetry	SYM	45	-	55	%	50%Vcc level
Output voltage	V_{OH}	90%Vcc	-	-	V	-
	V_{OL}	-	-	10%Vcc	V	-
Output load condition	L_CMOS	-	-	15	pF	-
Input voltage	V_{IH}	70%Vcc	-	-	V	-
	V_{IL}	-	-	30%Vcc	V	-
Rise time	tr	-	-	2	ns	20%Vcc to 80%Vcc level
Fall time	tf	-	-	2	ns	80%Vcc to 20%Vcc level
Start-up time	t_str	-	-	10	ms	t=0 at 90%Vcc
Phase jitter	tPJ	-	-	1	ps	Offset frequency:12 kHz to 20 MHz
Frequency aging	f_aging	-	-	-	$x10^{-6}$	Included in frequency tolerance

3.Timing chart




4.Test circuit

1) C-MOS load CL=15 pF




2) Current consumption



3) Condition

1. Oscilloscope
   Bandwidth should be 5 times higher than DUT's output frequency.
   Probe ground should be placed closely from test point and lead length should be as short as possible.
2. L_CMOS includes probe capacitance.
3. By-pass capacitor (0.1 µF + 10 µF) is placed closely between Vcc and GND.
4. Use the current meter whose internal impedance value is small.
5. Power Supply
   ・Start up time (0 %Vcc→90 %Vcc) of power source should be more than 150 µs.
   ・Impedance of power supply should be as low as possible.

5.External dimensions (Unit: mm)




Pin map

Pin	Connection
1	Vc
2	OE
3	GND
4	OUT
5	N.C.
6	Vcc

OE pin = "H" or "open": Specified frequency output.
OE pin = "L" : Output is high impedance.


6.Footprint(Recommended) (Unit: mm)



To maintain stable operation, provide a 0.1µF + 10µF by-pass capacitor at a location as near as possible to the power source terminal of the crystal product (between Vcc - GND).

7.Reflow profile

JEDEC STD-020D.01



8.Packing information

[1]Product number last 2 digits code(xx) description The recommended code is "00"

X1G0048610011xx

Code	Condition
00	1000pcs / Reel
01	Any Q'ty vinyl bag(Tape cut)
11	Any Q'ty / Reel

[2] Taping specification


Subject to EIA-481 & IEC-60286

(1) Tape dimensions

Material of the Carrier Tape : PS

Material of the Top Tape : PET+PE


Unit: mm



(2) Reel dimensions

Material of the Reel : PS

Unit: mm



9.Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
  / Space equipment (artificial satellites, rockets, etc.)
  / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.)
  / Medical instruments to sustain life
  / Submarine transmitters
  / Power stations and related
  / Fire work equipment and security equipment
  / Traffic control equipment
  / And others requiring equivalent reliability.

- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.

10.Contact us

http://www5.epsondevice.com/en/contact/