RECIPIENT

SPECIFICATIONS

Product No: **X1E000341015500**

MODEL : **FA-238A**

SPEC. No. : **A14-1474-1B**

DATE: **Mar. 9. 2015**

SEIKO EPSON CORPORATION

8548 Naka-minowa
Minowa-machi Kamiina-gun
Nagano-ken
399-4696 Japan

CHECKED K. Komine
Kenji Komine / TD Production Engineering Department Manager

CHECKED W. Ikegame
Wataru Ikegame / TD Production Engineering Department Senior Staff

CHECKED Ohashi
Hiroaki Ohashi / TD・CS Quality Assurance Department Manager

PREPARED T. Kurumizawa
Takashi Kurumizawa / TD・CS Quality Assurance Department Senior Staff

SPECIFICATIONS

1. Application

1) This document is applicable to the crystal FA-238A that are delivered to Neusoft Corporation from Seiko Epson Corp.
2) This product complies with RoHS Directive.
3) This Product supplied (and any technical information furnished, if any) by Seiko Epson Corporation shall not be used for the development and manufacture of weapon of mass destruction or for other military purposes.
   Making available such products and technology to any third party who may use such products or technologies for the said purposes are also prohibited.
4) This product listed here is designed as components or parts for electronics equipment in general consumer use.
   We do not expect that any of these products would be incorporated or otherwise used as a component or part for the equipment, which requires an systems, and medical equipment, the functional purpose of which is to keep extra high reliability, such as satellite, rocket and other space life.
5) This product conforms to automotive part standard " AEC-Q200 ".

This FA-238A is authorized for Use of Car Audio for automobile only.

2. Product No. / Model

The product No. of this crystal unit is X1E000341015500.
The model is FA-238A.

3. Packing

It is subject to the packing standard of Seiko Epson Corp.

4. Warranty

Defective parts which originate with us are replaced free of charge in the case of defects being found with 12 months after delivery.

5. Amendment and/or termination

Amendment and/or termination of this specification is subject to the agreement between the two parties.

6. Contents

Item No.	Item	Page
[1]	Absolute maximum ratings	2
[2]	Operating range	2
[3]	Static characteristics	2
[4]	Environmental and mechanical characteristics	3
[5]	Dimensions and circuit	4
[6]	Recommended soldering pattern and marking layout	5
[7]	Notes	6

[1] Absolute maximum ratings

No.	Item	Symbol	Rating value			Unit	Note
			Min.	Typ.	Max.		
1	Storage temperature range	T_stg	- 40		+ 125	°C	Depends on the Environmental characteristics specifications.

[2] Operating range

No.	Item	Symbol	Rating value			Unit	Note
			Min.	Typ.	Max.		
1	Operating temperature range	T_use	-40		+125	°C	Depends on the Motional resistance and Frequency temperature characteristics specifications.
2	Level of drive	DL	10	100	200	μW	Recommended level 10~100 μ W

[3] Static characteristics

No.	Item	Symbol	Value	Unit	Conditions
1	Nominal Frequency	f_nom	62.4	MHz	Fundamental
2	Frequency tolerance	f_tol	± 20	$\times 10^{-6}$	CL = 8 pF Ta = + 25 ± 3 °C DL : 100 μW Not include aging
3	Motional resistance	R1	50 Max.	Ω	π circuit IEC 60444-2 Ta = - 40 °C ~ + 125 °C DL : 100 μW
4	Shunt capacitance	C0	5 Max.	pF	π circuit and N.A.
5	Frequency temperature characteristics	f_tem	± 50	$\times 10^{-6}$	Ta = - 40 °C ~ + 125 °C (Ref. at Ta = + 25 °C ± 3 °C) DL : 100 μW
6	Unwanted responses	RS/R1	6 Min.	dB	f_nom ±10 %
7	Isolation resistance	IR	500 Min.	MΩ	DC 100 V, 60 seconds between each terminals (#1, #3)
8	Frequency Aging	f_age	±5 Max.	$\times 10^{-6}$/year	Ta = + 25 °C ± 3 °C (first year, no bias)

[4] Environmental and mechanical characteristics


(The company evaluation condition : We evaluate it by the following examination item and examination condition.)

No.	Item	Value * 1 * 2 $\Delta f / f\ [1 \times 10^{-6}]$	Test Conditions
1	Shock	* 3 ± 5	100 g dummy Jig (Epson Standard) drop from 1 500 mm height on the Concrete 3 directions 10 times
2	Vibration	* 3 ± 5	10 Hz to 55 Hz amplitude 0.75 mm 55 Hz to 500 Hz acceleration 98 m/s^2 10 Hz → 500 Hz → 10 Hz 15 min./cycle 6 h (2 hours , 3 directions)
3	High temperature storage	* 3 ± 10	+ 125 °C × 1 000 h
4	Low temperature storage	* 3 ± 5	- 40 °C × 1 000 h
5	Temperature cycle	* 3 ± 10	- 40 °C ↔ + 125 °C 30 minutes at each temp. 1 000 cycle
6	Temperature humidity storage	* 3 ± 5	+ 85 °C × 85 %RH × 1 000 h
7	Resistance to soldering heat	± 3	For convention reflow soldering furnace (3 times)
8	Substrate bending	No peeling-off at a soldered part	Bend width reaches 3.0 mm and hold for 20 s ± 1 s × 1 time Ref. IEC 60068-2-21
9	Shear	No peeling-off at a soldered part	10 N press for 10 s ± 1 s Ref. IEC 60068-2-21
10	Pull – off	No peeling-off at a soldered part	10 N press for 10 s ± 1 s Ref. IEC 60068-2-21
11	Solderability	Terminals must be 95 % covered with fresh solder.	Dip termination into solder bath at + 235 °C ±5 °C for 5 s (Using Rosin Flux)

< Notes >


1. * 1 Each test done independently.
2. * 2 Measuring 2 h to 24 h later leaving in room temperature after each test.
3. * 3 Item No.1 to No.6 shall be tested after following pre conditioning.
   Measuring 24 h later leaving in room temperature after Pre conditioning.
   Pre conditioning : Reflow 3 times.
4. Item No.1 to No.7, Shift motional resistance at after above tests should be less than 20 % or less than 10 Ω.

◆Reflow condition (follow to IPC/JEDEC J-STD-020D.1)




[5] Dimensions and Circuit

1) Dimension



Terminal Au plate : 1.5 μm Max.

2) Circuit




1 , # 3 : XTAL
2 , # 4 : GND（are connected to the cover）


Type : FA-238A	Terminal treatment : Au plate	Unit : 1 = 1 mm

[6] Recommended soldering pattern and Marking layout

1)Recommended soldering pattern



2) Marking layout



Production month

January	February	.....	October	November	December
1	2	.....	X	Y	Z

- Nominal frequency is only one example.
- Nominal frequency omits the figure below the first place of decimals.
  ex) 62.4 MHz ..... [624]
- The above marking layout shows only marking contents and their approximate position and it is not for font, size and exact position.

Type : FA-238A	Unit : 1 = 1 mm

[7] Notes

1. Max three (3) times re-flow is allowed. Its recommended to manually solder when not enough/no solder detected.
   (Using soldering iron at +350 °C Max × within 5 seconds)

2. Too much exciting shock or vibration may cause deterioration on damage.
   The product may damage depends on the condition such as a shock in assembly machinery.
   Please check your process condition in advance to minimize and maintain the shock level.

3. It is recommended to do patterning to the oscillator as short as possible. Abnormal oscillation may happened if the line is too long.

4. Please normal temperature (+15 °C to +35 °C) and normal humidity (25 to 85 %RH) as much as possible for the frequency accuracy securing.
   Storing the crystal products under higher or lower temperature or high humidity for long period may affect frequency stability or solderability. Check conditions prior to use.

5. This product may be affected to ultrasonic cleaning.. Check conditions prior to use.


6. When do the be dewy of the oscillation circuit board, the frequency change or the oscillation stop is generated.
   Please use it under the condition without the be dewy.

7. Few data or readings taken at user side may be different from our company's data.
   Confirmation of the different value is necessary before application.

8. To avoid malfunction, no pattern across or near the crystal is allowed.

9. Start up time of oscillation may be increased or no oscillation may occur unless adequate negative resistance is allocated in the oscillation circuit In order to avoid this, please provide enough negative resistance to the circuit design.

How to check the negative resistance



(1) Connect the resister(R) to the circuit in series with the crystal unit.

(2) Adjust R so that oscillation can start (or stop).

(3) Measure R when oscillation just start (or stop) in above (2).

* Get the negative resistance
  -R = R + Motional resistance (R1).
* Recommended -R
  [-R] > R1 × 10

TAPING SPECIFICATION

1. APPLICATION

This document is applicable to FA-238A

2. CONTENTS

Item No.	Item	Page
[1]	Taping specification	1 to 2
[2]	Inner sleeve	3
[3]	Shipping carton	
[4]	Marking	4
[5]	Quantity	
[6]	Storage environment	
[7]	Handling	


[1] Taping specification

Subject to EIA-481 & IEC-60286

(1) Tape dimensions TE0804L

Material of the Carrier Tape : PS


Material of the Top Tape : PET+PE



(2) Reel dimensions


(a) Center material : PS

(b) Material of the Reel : PS




(3) Packing

(a) Tape & Reel



(b) Start & End Point



Item		Empty Space
Tape Leader	Top Tape	Min. 1 000 mm
	Carrier Tape	Min. 100 mm
Tape Trailer	Top Tape	Min. 0 mm
	Carrier Tape	Min. 160 mm

(4) Peel force of the cover tape


① angle : cover tape during peel off and the direction of unreeling shall be 165° to 180°.

② peel speed : 300 mm / min.


③ strength : 0.1 to 1 N.

[2] Inner sleeve

a) Packing to antistatic bag



b) Packing to inner sleeve




* There is also a case to put the two reel.

[3] Shipping Carton

・Put inner sleeve into an outer box.

・If there are room in the outer box, material is put in a shock absorbing together.



[4] Marking

(1) Reel marking

- Reel marking shall consist of :

1) Parts name
2) Quantity
3) Manufacturing Date or symbol
4) Manufacturer’s Date or symbol
5) Others (if necessary)

(2) Shipping carton marking

- Shipping carton marking shall consist of :

1) Parts name
2) Quantity

[5] Quantity

- 4 000 pcs./reel

[6] Storage environment

(1) To storage the reel at +15 °C to +35 °C , 25 %RH to 85 %RH of Humidity.
(2) To open the packing just before using.
(3) Not to expose the sun.
(4) Not to storage with some erosive chemicals.
(5) Nothing is allowed to put on the reel or carton to prevent mechanical damage.

[7] Handling

To handle with care to prevent the damage of tape, reel and products.

- PROCESS QUALITY CONTROL -

2015.02.23


No.A-1302-01-AAE-2 **SMD TYPE AT STRIP CRYSTAL FA-238A** FA238A_Q_0001

Manufacturing process chart	No.	Section	Standards	Inspection,Control Items	Inspection Methods	Instrument	Record
CRYSTAL BLOCK	1	Inspection Section	Purchasing Specification Incoming Inspection Standard	Dimension Outer Appearance Inner Appearance	Sampling 〃 〃	Length Gauge Visual Inspection Visual Inspection	In-Coming Inspection Data Sheet
◇1 In-coming Inspection	1'	Inspection Section	〃	Dimension Outer Appearance	Sampling 〃	Comparator Microscope	〃
② Wafer Cutting	2	Ploduction Section	Manufacturing Instruction Sheet	Cut Angle Wafer Thickness	Sampling 〃	X-ray Radio Grafic Comparator	Process Data Sheet
③ Wafer Lapping	3	Ploduction Section	〃	Frequency Wafer Thickness	Sampling 〃	Blank Osillator Comparator	〃
Ceramic Package ④ Chip Cutting	4	Ploduction Section	〃	Dimension	Sampling	Comparator	〃
⑤ Etching	5	Ploduction Section	〃	Frequency Outer Appearance	Sampling 〃	Blank Osillator Microscope	〃
◇1' In-coming Inspection ⑥ Deposition	6	Ploduction Section	〃	Frequency Outer Appearance	Sampling 〃	Blank Osillator Microscope	〃
Lid ⑦ Mounting	7	Ploduction Section	〃	Outer Appearance	100% Inspection	Microscope	〃
In-coming ◇1' Inspection ⑧ Frequency Adjustment	8	Ploduction Section	〃	Frequency	Sampling	NetworkAnalyzer	〃
⑨ Welding	9	Ploduction Section	〃	Outer Appearance	100% Inspection	Microscope	〃
◇10 Leak Test	10	Ploduction Section	〃	Package Leak	100% Inspection	Leak Tester	〃
⑪ Marking	11	Ploduction Section	〃	Outer Appearance	Sampling	Microscope	〃
◇12 Characteristic Inspection	12	Ploduction Section	〃	Crystal Impedance Frequency Insulation Resistance Temp. Characteristic Outer Appearance	100% Inspection 〃 〃 Sampling 100% Inspection	Inspection M/C 〃 〃 〃 Microscope	〃
◇13 Out-going Inspection	13	Inspection Section	Out-going Inspection Standard	Crystal Impedance Frequency Insulation Resistance Outer Appearance	Sampling 〃 〃 〃	Inspection M/C 〃 〃 Microscope	Out-going Inspection Data Sheet
⑭ Taping	14	Ploduction Section	Manufacturing Instruction Sheet	Tape-Peel Strength	Sampling	Peeling Force Tester	Process Data Sheet
⑮ Packing	15	Ploduction Controle Section	Manufacturing Instruction Sheet Packing Instruction Sheet	Destination Quantity	——	——	Delivery Slip


Structure Diagram 構造図

Model 型式	**FA-238A**	
Document No. 管理№.	A-130*-1	FA238A_D_0001

■Under 27 MHz (3 Point Bonding) 27MHz 以下 3 点固定



■Over 27 MHz (2 Point Bonding) 27MHz 超 2 点固定



④	Crystal chip 水晶片
③	Crystal Adhesive 水晶接着
②	Package パッケージ
①	Lid リッド
No.	Name of Part 部品名

RELIABILITY TEST DATA

Product Name : FA-238A

The Company evaluation condition

We evaluate environmental and mechanical characteristics by the following test condition . **No. DTA-1314-1**

No.	ITEM	TEST CONDITIONS	VALUE *1 *2 Δ f / f [1 × 10^{-6}]	TEST Qty [n]	FAIL Qty [n]
1	Drop	100g dummy Jig (Epsontoyocom Standard) drop from 1500 mm height on the Concrete 3 directions 10 times	*3 ± 5	22	0
2	Vibration	10 Hz to 55 Hz amplitude 0.75 mm 55 Hz to 500 Hz acceleration 98 m/s2 10 Hz→500 Hz→10 Hz 15 min./cycle 6 h (2 hours , 3 directions)	*3 ± 5	22	0
3	High temperature storage	+125 °C × 1 000 h	*3 ± 10	22	0
4	Low temperature storage	-40 °C × 1 000 h	*3 ± 5	22	0
5	Temperature cycle	-40 °C ⇔ + 125 °C 30 min at each temp. 1000 cycles	*3 ± 10	22	0
6	Temperature humidity storage	+85 °C × 85 %RH × 1 000 h	*3 ± 5	22	0
7	Resistance to soldering heat	For convention reflow soldering furnace (3 times)	± 3	22	0
8	Substrate bending	Bend width reaches 3.0 mm and hold for 20 s ± 1 s × 1 time Ref. IEC 60068-2-21	No peeling-off at a soldered part	11	0
9	Shear	10 N press for 10 s ± 1 s Ref. IEC 60068-2-21	No peeling-off at a soldered part	11	0
10	Pull – off	10 N press for 10 s ± 1 s Ref. IEC 60068-2-21	No peeling-off at a soldered part	11	0
11	Solderability	Dip termination into solder bath at +230°C ± 10 °C for 5 s (Using Rosin Flux)	Termination must be 95 % covered with fresh solder	11	0

Notes

1. *1 Each test done independently.
2. *2 measuring 24 h later leaving in room temperature after each test.
3. *3 Item No.1 to No.6 shall be tested after following pre conditioning.
   Measuring 24 h later leaving in room temperature after Pre conditioning.
   Pre conditioning : Reflow 5 times.
4. Item No.1 to No.7, Shift motional resistance at after above tests should be less than 20 % or less than 10 Ω.

Qualification Data


Product Name : FA-238A

Δ f / f

No. DTA-1314-2


1. Drop

100g × 1500 mm ×
3 directions × 10 times




2. Vibration

10 Hz to 500 Hz acceleration 98 m/s^2
15 min /cycle, 8cycle ×3 directions




3. High temp. storage

+125 °C × 1 000 h




4. Low temp. storage

-40 °C × 1 000 h




5. Temp. cycle

-40 °C ⇔ +125 ℃ 1000 cycles




6. Temp. humidity storage

+85 °C × 85 %RH × 1 000 h



7. Resistance to

soldering heat
For convention reflow
soldering furnace (5 times)



Qualification Data


Product Name : FA-238A

Δ CI

No. DTA-1314-3


1. Drop

100g × 1500 mm ×
3 directions × 10 times




2. Vibration

10 Hz to 500 Hz acceleration 98 m/s^2
15 min /cycle, 8cycle ×3 directions




3.High temp. storage

+125 °C × 1 000 h




4. Low temp. storage

-40 °C × 1 000 h




5.Temp. cycle

-40°C ⇔+125°C 1000cycles




6. Temp. humidity storage

+85 °C × 85 %RH × 1 000 h



7. Resistance to
soldering heat
For convention reflow
soldering furnace (5 times)



Qualification Data