PRODUCT SPECIFICATION SHEET



Customer	-		
Customer P/N	TBA		
Product Type	Temperature Compensated Crystal Oscillator		
Part Number	9T2601E001	Version	S0
Part Description	SMD TCXO 2.0 x 1.6		
Nominal Frequency	26.000000MHz		

Prepared	Han Shuang
Reviewed	Kuro Peng
Approved	Jay Lee
Date	2020-9-14

Customer's Approval & Date：

廣東惠倫晶體科技股份有限公司
中国广东省东莞市黄江镇东环路鸡啼岗段68号
68 Donghuan Road, Jitigang Village, Huangjiang, Dongguan, Guangdong Province, P. R. China
WEB : http://www.dgylec.com/
TEL : +86 (0) 769 - 38879888
FAX : +86 (0) 769 - 38879889
EMAIL : yl@dgylec.com

RoHS COMPLIANT

Pb Lead-Free

Moisture Sensitivity Level 1

CONTENTS

#	Item	Page
1	History of Specification Revision	3
2	Electrical Specification	4
	2.1 Operation condition	4
	2.2 Output characteristics	4
	2.3 Frequency characteristics	4
	2.4 Phase noise characteristics	5
3	Product Design	6
	3.1 Package dimensions and pad functions	6
	3.2 Recommended land pattern	6
	3.3 Recommended reflow profile	6
4	Testing Circuit	7

1. History of Specification Revision

Ver.	Contents	Date	Reviser	Remark
S0	Initial release	2020-9-14	Han Shuang	

2. Electrical Specifications

2.1 Operation conditions

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency		26.000000		MHz	
2	Supply voltage (V_{CC})	1.7	1.8	3.3	V	
3	Current consumption	-	-	1.5	mA	
4	Operating temperature range	-40	-	+85	°C	
5	Storage temperature range	-40	-	+90	°C	

2.2 Output characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Output type		Clipped sine wave		-	Decoupling capacitor is required in external circuit
2	Standard output Load		10 KΩ//10 pF		-	
3	Output level	0.8	-	1.5	V_{pp}	
4	Duty cycle	40	50	60	%	
5	Harmonics	-	-	-5	dBc	
6	Start-up time vs. frequency	-	-	2.0	ms	Within ±1.0 ppm of final frequency
7	Start-up time vs. output level	-	-	2.0	ms	Reach 90% of final Vpp output level

2.3 Frequency characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency		26.000000		MHz	
2	Frequency tolerance before reflow	-1.0	-	+1.0	ppm	At 25±2°C, before reflow, refer to nominal frequency
3	Frequency tolerance after reflow	-2.0	-	+2.0	ppm	At 25±2°C, after 2 times of reflow, refer to nominal frequency (See below NOTE 1)
4	Frequency stability vs. temperature	-0.5	-	+0.5	ppm	Refer to frequency at 25° C within operating temperature range
5	Frequency stability vs. supply voltage	-0.2	-	+0.2	ppm	±5% V_{CC} variation
6	Frequency stability vs. load variation	-0.2	-	+0.2	ppm	±5% load variation
7	Aging over 1st year	-1.0	-	+1.0	ppm	At 25±°C

NOTE 1: Frequency is measured after 24 hours after reflow cycles.


2. Electrical Specifications (Cont.)

2.4 Phase noise characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Phase noise at 10Hz offset			-83	dBc/Hz	
2	Phase noise at 100Hz offset			-108	dBc/Hz	
3	Phase noise at 1kHz offset			-135	dBc/Hz	
4	Phase noise at 10kHz offset			-148	dBc/Hz	
5	Phase noise at 100kHz offset			-148	dBc/Hz	
6	Phase noise at 1MHz offset			-148	dBc/Hz	


3. Product Design

3.1 Package dimensions and pad functions




Pad	Function	Symbol
1	NC or GND (Ground recommended)	NC
2	Ground	GND
3	Output	OUT
4	Supply voltage	V_{CC}

3.2 Recommended land pattern




Unit : mm

3.3 Recommended reflow profile



(1) Total time : 360 sec. Max.
(2) Solder melting point : 225℃

4. Testing Circuit



External Components:

Parts	Function	Recommended
C1	AC noise bypass for V_{CC}	10nF
C3	DC block for output	10nF
RL	Load resistance	10KΩ
CL	Load capacitance	10pF