PRODUCT SPECIFICATION SHEET



Customer	–		
Customer P/N	TBA		
Product Type	Temperature Compensated Crystal Oscillator		
Part Number	3TN2740001	Version	S0
Part Description	SMD TCXO 3.2 x 2.5		
Nominal Frequency	27.456000MHz		

Prepared	Li Xiang
Reviewed	Jin Zhe
Approved	Liu Feng
Date	2023/9/1

Customer's Approval & Date：

广东惠伦晶体科技股份有限公司
中国广东省东莞市黄江镇东环路鸡啼岗段68号
68 Donghuan Road, Jitigang Village, Huangjiang, Dongguan, Guangdong Province, P. R. China
WEB : http://www.dgylec.com/
TEL : +86 (0) 769 - 38879888
FAX : +86 (0) 769 - 38879889
EMAIL : yl@dgylec.com

RoHS COMPLIANT

Pb Lead-Free

Moisture Sensitivity Level 1

CONTENTS

#	Item	Page
1	History of Specification Revision	3
2	Electrical Specifications	4
	2.1 Operation conditions	4
	2.2 Output characteristics	4
	2.3 Frequency characteristics	4
	2.4 Phase noise characteristics	4
3	Product Design	5
	3.1 Package dimensions and pad functions	5
	3.2 Recommended land pattern	5
	3.3 Recommended reflow profile	5
4	Testing Circuit	6

ATTENTION

[1] If you intend to use products on the controlling equipment that relate to medical, aeronautical, aerospace, military science, space and etc., please make sure to let us know your intentions in advance.

[2] Ultrasonic related process may cause damage to crystal blank by resonance itself. If ultrasonic related process is used, we strongly recommend to assess the damage risk under related ultrasonic conditions before use in production.

1. History of Specification Revision

Ver.	Contents	Date	Reviser	NOTE
S0	Initial release	2023/9/1	Li Xiang	

2. Electrical Specification

2.1 Operation conditions

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency		27.456000		MHz	-
2	Supply voltage (V_{DD})	1.68	-	3.63	V	-
3	Current consumption	-	-	2.0	mA	-
4	ESD		HBM＞2000V		-	JESD22-A114-B
5	MSL		Level 1		-	IPC/JEDEC J-STD-033C
6	Operating temperature range	-30	-	+85	℃	-
7	Storage temperature range	-40	-	+90	℃	-

2.2 Output characteristics

#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Output type		Clipped sine wave		-	Decoupling capacitor is required in external circuit
2	Standard output Load		10 KΩ//10 pF		-	-
3	Output level	0.8	-	-	V_{pp}	-
4	Duty cycle	40	50	60	%	-
5	Harmonics	-	-	-5	dBc	-
6	Start-up time vs. frequency	-	-	2.0	ms	Within ±0.5 ppm
7	Start-up time vs. output level	-	-	2.0	ms	90% of Vpp

2.3 Frequency characteristics


#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Nominal frequency		27.456000		MHz	-
2	Frequency tolerance after reflow	-2.0	-	+2.0	ppm	At 25±2°C after 2 times reflow, refer to nominal frequency
3	Frequency stability vs. temperature	-0.5	-	+0.5	ppm	Refer to frequency at 25°C within operating temperature range
4	Frequency slope vs. temperature	-0.1	-	+0.1	ppm/°C	From -20 to +70℃.
5	Frequency stability vs. supply voltage	-0.2	-	+0.2	ppm	±5% V_{DD} variation
6	Frequency stability vs. load variation	-0.2	-	+0.2	ppm	±5% load variation
7	Frequency Aging	-1.0	-	+1.0	ppm/First year	-

2.4 Phase noise characteristics


#	Parameters	Min.	Typ.	Max.	Unit	Remark
1	Phase noise at 1kHz offset	-	-130	-	dBc/Hz	


3. Product Design

3.1 Package dimensions and pad functions



Unit : mm






Lateral view


Pad	Function	Symbol
1	NC or GND (Ground recommended)	NC
2	Ground	GND
3	Output	OUT
4	Supply voltage	V_{DD}

3.2 Recommended land pattern




Unit : mm

3.3 Recommended reflow profile



(1) Total time : 360 sec. Max.
(2) Solder melting point : 225℃

4. Testing Circuit



External Components:

Parts	Function	Recommended
C1	AC noise bypass for V_{DD}	10nF
C3	DC block for output	10nF
RL	Load resistance	10KΩ
CL	Load capacitance	10pF