TXC CORPORATION

www.txccorp.com

SPECIFICATION FOR APPROVAL

CN: 1709016862

CUSTOMER	:	
PRODUCT TYPE	:	SMD SEAM SEALING XTAL 5.0 × 3.2
NOMINAL FREQ.	:	8.000000MHz
TXC P/N	:	AB08000303
REVISION	:	A1
CUSTOMER P/N	:	
PM / SALES	:	
DATE	:	
CUSTOMER CONFIRMATION	:	

(1) TXC requires one copy returned with signature and title of authorized individual that signifies acceptance of the attached specifications.

(2) Orders received and accepted by TXC after return of signed copy of specification will be produced per these specifications.

(3) Any changes to these specifications must be agreed upon by both parties and new revision of the Product Specification Sheet will be issued.

(4) Any issuance of purchase order prior to consigning back the Approval page of "Specification Sheets" from customers will be regarded as the agreement on the contents of these specifications.

MSL:Level 1

RoHS Compliant

(for glass crystal only:Pb used in sealing glass material is exempt from EU directive)

TXC confidential and proprietary document

TXC CORPORATION

www.txccorp.com

PRODUCT SPECIFICATION SHEET

CN: 1709016862

PRODUCT TYPE	:	SMD SEAM SEALING XTAL 5.0 × 3.2
NOMINAL FREQ.	:	8.000000MHz
TXC P/N	:	AB08000303
REVISION	:	A1

PE/RD	QA	MFG
Wen yuan Chang Wen yuan Chang	ZhongLin Wu ZhongLin Wu	zhi jun Wu Zhi jun Wu
7-Feb-17	*7-Feb-17*	*7-Feb-17*

NOTE:

(1)The green product standard set by TXC is based upon the international standards. Related information is publicly described on the TXC's Website, and updated regularly. The document is compliant with the latest green product quality system directives at the time.

(2)Revision "Sx" is for engineering samples only. PE/RD's approval required.

(3)Revision "Ax" is production ready. PE, QA and MFG's approval required

MSL:Level 1

RoHS Compliant

(for glass crystal only:Pb used in sealing glass material is exempt from EU directive)

TXC confidential and proprietary document

Rev	Revise page	Revise contents	Date	Ref.No.	Revise
S1	N/A	Initial released	21-Oct-16	N/A	Xiaoyan J
A1	N/A	S Turn A	7-Feb-17	N/A	Xiaohua Zl

TXC confidential and proprietary document

■ ELECTRICAL SPECIFICATIONS

Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurement and tests are as follow:

Ambient temperature : 25±5℃

Relative humidity : 40%~70%

If there is any doubt about the results, measurement shall be made within the following limits:

Ambient temperature : 25±3℃

Relative humidity : 40%~70%

Measure equipment

Electrical characteristics measured by S&A 250B or equivalent.

Crystal cutting type

The crystal is using AT CUT (thickness shear mode).


Unit Weight:

0.046±0.002 g/pcs

	Parameters	SYM.	Electrical Spec.				Notes
			MIN	TYPE	MAX	UNITS	
1	Nominal Frequency	FL		8.000000		MHz	-
2	Oscillation Mode	-		Fundamental		-	-
3	Load Capacitance	CL		20		pF	-
4	Frequency Tolerance	-		±30		ppm	at 25 ℃ ± 3 ℃
5	Frequency Stability	-		±100		ppm	Over Operating Temp. Range (Reference 25℃)
6	Operating Temperature	-	-40	~	125	℃	-
7	Aging	-	-5	~	5	ppm	1st Year
8	Drive Level	DL	-	50	100	μW	-
9	Effective Resistance	Rr	-	-	150	Ω	-
10	Shunt Capacitance C0	C0	-	-	7	pF	-
11	Insulation Resistance	-	500	-	-	MΩ	at DC 100V
12	Storage Temperature Range	-	-40	~	125	℃	-


TXC confidential and proprietary document

■ DIMENSIONS



*Coplanarity of solderable areas Camber 0.10 mm Max

■ MARKING




Production location: China or Taiwan

■ SUGGESTED REFLOW PROFILE


Total time : 200 sec. Max.

Solder melting point :220 ℃



TXC confidential and proprietary document


STRUCTURE ILLUSTRATION



NO	COMPONENTS	MATERIALS	FINISH/SPECIFICATIONS
1	Lid	Kovar (Fe/Co/Ni)	-
2	Package	Ceramic (Al_2O_3) + Kovar (Fe/Co/Ni)+ Ag/Cu	-
3	PAD	Au	Tungsten metalize + Ni plating + Au plating
4	Crystal blank	SiO_2	-
5	Conductive adhesive	Ag+Silicon	-
6	Electrode	Noble Metal	-


TXC confidential and proprietary document


■ PACKING



DIMENSIONS	A	B	C	D	E	F	G	H	
	1.65±0.10	5.40±0.10	3.50±0.10	8.00±0.10	12.00±0.30	4.00±0.10	1.55±0.10	1.75±0.10	(UNIT :

REMARK :





DIMENSIONS	L	L1	W	W1	pcs / Reel (UNIT : mm)
	180±1.00	13±0.50	16.5±0.20	12±0.10	Standard Reel Quantity is 1,000 pcs per reel


TXC confidential and proprietary document

■ RELIABILITY SPECIFICATIONS (AEC-Q200 Compliant)


1.Mechanical Endurance

No.	Test Item	Test Methods		REF.DC
1	Drop Test	120 cm height, 20 times on Stainless Plate .		JIS C 67
1	Mechanical Shock	Device are shocked to half sine wave (5000 G) three mutually perpendicular axes each 3 times. 0.3m sec. duration time		MIL-STD- Method 2
1	Vibration	Frequency range Amplitude Sweep time Perpendicular axes each test time	10 ~ 2000 Hz~10 Hz 1.52 mm/20G 20 minute 4 Hrs (Total test time 12 Hrs)	MIL-STD- Method 2
1	Solderability	Temperature Immersing depth Immersion time Flux	245 ℃ ± 5℃ 1.25 mm 5 ± 1 seconds Rosin resin methyl alcohol solvent (1 : 4)	J-STD-0
2	Terminal Strength	Mount on PCB board and shear strength 1.8kg for 60 sec.		AEC-Q200
2	Board Flex	Duration Time: 60 sec, Deviation: 3mm		AEC-Q200


2.Environmental Endurance

No.	Test Item	Test Methods		REF. DC
2	Resistance To Soldering Heat	Pre-heat temperature Pre-heat time Test temperature Test time	125 ℃ 60 ~ 120 sec. 260 ± 5 ℃ 10 ± 1 sec.	MIL-STD Method 2
2	High Temp. Storage	+ 125 ℃ ± 3 ℃ for all 1000 Hrs.		MIL-STD- Method 1
2	Low Temp. Storage	- 40 ℃ ± 3 ℃ for all 1000 Hrs.		JIS C 67
2	Thermal Shock	Total 1000 cycles of the following Thermal Shock : 		MIL-STD- Method 1
3	Temperature Cycle	Total 1000 cycles of the following temperature cycle : - 40℃ ± 3 to 125℃ ± 3 , Dwell time:15min.		JESD 2 Method JA
3	Biased Humidity	+ 85℃ ± 3℃ , RH 85% , 1000 Hrs.		MIL-STD- Method 1
3	Moisture Resistance	20 cycles (+25℃~65℃ , 80%~100% RH) , 24hrs/cycle.		MIL-STD Method 1
3	Operational Life	+ 125 ℃ ± 3 ℃ for 1000 Hrs.		MIL-STD- Method 1

TXC confidential and proprietary document




TXC confidential and proprietary document



2

TXC confidential and proprietary document

TXC confidential and proprietary document



TXC confidential and proprietary document



TXC confidential and proprietary document