CF2600C3IS3D156.250000

High Performance Differential Oscillator

Features

Crystal Oscillator P/N: **CF2600C3IS3D156.250000**
Frequency: **156.25MHz**
Output Signal Type: **LVDS**
Supply Voltage: **3.3V** ±10%
RMS Phase Jitter: **0.2ps** 12KHz ~ 20MHz Frequency Band
Frequency Stability: **±20 ppm**
Operating temperature Range: -40 ~ +85℃
Storage Temperature Range: -55 ~ +125℃
Environmental Compliance: RoHS/REACH/Pb-free/Halogen Free/MSL 1

Applications


Network equipment (Router, Switch, Optical module, etc.)
Telecom, instrumentation, storage, server

Pin Description

Pin#	Pin Name	I/O	Function
1	OE	Input	H or Open: Enable Output; L: Output High Impedance
2	NC	NA	No Connection
3	GND	Ground	Ground
4	OUT+	Output	Oscillator Output
5	OUT-	Output	Complementary Oscillator Output
6	VDD	Power	Power Supply Voltage

Pin Assignments

Top View



Ordering Information


Part/Order Number	Marking	Package	MPQ	Temperature
CF2600C3IS3D156.250000	6d156	3225	3000	-40 ~ +85℃

Electrical Characteristics


Parameters	Symbol	Condition	Min.	Typ.	Max.	Unit
Supply Voltage	Vdd		2.97	3.3	3.63	V
Output Frequency	Fout			156.250000		MHz
Frequency Stability		**Note 1**		±20		ppm
Input Voltage High	VIH		70%			Vdd
Input Voltage Low	VIL				30%	Vdd
Duty Cycle	DC	=Tw/Tcycle *100%	45		55	%
Current Consumption	Idd	OE = High			35	mA
OE Disable Supply Current	I_od	OE=Low			100	uA
Output High Voltage	VOH			1.43	1.6	V
Output Low Voltage	VOL		0.9	1.1		V
Differential Output Voltage	Vod		250	350	450	mV
Delta Vod	ΔVod				50	mV
Output Offset Voltage	Vos		1.12	1.25	1.38	V
Delta Vos	ΔVos				50	mV
Rise/Fall Time	Tr, Tf	20%, 80%			0.35	ns
Start-up Time	T_start				8	ms
OE Enable Time	T_oe				2	ms
OE Disable Time	T_od				200	ns
RMS Phase jitter	RMS	12KHz ~ 20MHz			0.2	ps

Note 1: Includes conditions: initial tolerance, operating temperature, rated power supply voltage, and load changes

Waveform Diagrams




Termination Diagrams



Dimensions and Patterns


Unit: mm




Top View



Side View



Land Pattern




Bottom View


Marking



Tape and Reel


Unit: mm





Reflow Profile

Temperature(℃)



Time(s)

Stage	Temperature (℃)	Time (second)
Preheat	150-200	60 ~ 120
Primary Heat	217	60 ~ 150
Peak	260	10

Revision History

Revisions	Release Date	Change Summary
0.1	Feb.13,2025	Initial Release