1. Device Name KDS VC-TCXO
2. Model Name DSA321SDA
3. Nominal Frequency 50.000 MHz
4. Mass 0.03g max.
5. Absolute Maximum Ratings

	Item	Symbol	Rating	unit
1	Supply Voltage	V_{CC}	-0.3 ~ +6.0	V
2	Storage Temperature Range	$T_{_STG}$	-40 ~ +85	°C

6. Recommended Operating Conditions

	Item	Symbol	min.	typ.	max.	unit
1	Supply Voltage	V_{CC}	+3.135	+3.3	+3.465	V
2	Load Impedance (resistance part)	L_{oad}_R	9	10	11	kΩ
	(parallel capacitance)	L_{oad}_C	9	10	11	pF
3	Control Voltage Range	V_{CONT}	+0.4	+1.4	+2.4	V
4	Operable Temperature Range	$T_{_OPR}$	-40	-	+85	°C


7. Electrical Characteristics

(T_A=-40 ~ +85 °C, L_{oad}_R//C=10kΩ//10pF, V_{CC}=+3.3V, V_{CONT}=+1.4V unless otherwise noted)

	Item	Conditions	Limits			unit	Notes
			min.	Typ	max.		
1	Current Consumption		-	-	2.0	mA	
2	Output Level		0.8	-	-	V_{P-P}	1
3	Symmetry	GND level(DC cut)	40/60	-	60/40	%	
4	Harmonics		-	-	-5	dBc	
5	Frequency Stability						
	1.Tolerance	After 2 times reflow Ref. to Nominal Frequency	-	-	±1.5	ppm	2
	2.vs Temperature	T_A=-40 ~ +85 °C V_{CONT}=+1.4V Ref. to Frequency(T_A=+25°C)	-	-	±1.0	ppm	
	3.vs Slope	T_A=-40 ~ +85°C	-	-	±0.15	ppm/°C	
	4.vs Supply Voltage	V_{CC}=+3.3V±5%	-	-	±0.2	ppm	
	5.vs Load Variation	L_{oad}_R//C=(10kΩ//10pF)±10%	-	-	±0.2	ppm	
	6.vs Aging	T_A=Room ambient	-	-	±1.0	ppm/year	
6	Start up	@90% of final Vout level	-	-	2.0	ms	
7	Frequency Control						
	1.Control Range	V_{CONT}=+0.4V ~ +2.4V(Ref:+1.4V)	±3	-	±5	ppm	3
	2.Input Resistance		500	-	-	kΩ	
8	SSB Phase Noise	Relative to F0 level offset 100Hz	-	-	-110	dBc/Hz	
		Relative to F0 level offset 1kHz	-	-	-125	dBc/Hz	
		Relative to F0 level offset 10kHz	-	-	-135	dBc/Hz	
		Relative to F0 level offset 100kHz	-	-	-145	dBc/Hz	

Notes
1. Clipped sine wave (DC-coupled)
2. Please leave after reflow in 2-hour or more at room ambient
3. Positive slope (Frequency becomes high in proportion to frequency control voltage.)

8. Outline, Pin Connections




Pin Connections

Pin No.	Connection
#1	Vcont
#2	GND
#3	OUTPUT
#4	Vcc

Marking
(1) Frequency 50.00(MHz, 4digits)
(2) Model code S
(3) EIA Date code Year(1digit)+Week(2digits)
e.g. 2009/1/1 → 901

unit : mm
Dimensional Tolerance: ±0.15
(Unless otherwise noted)

9. Measurement Circuit



TITLE	Remark		
VC-TCXO SPECIFICATION			
Date	Spec. No.	Rev.	Page
2009/02/18	ZQ04216	-	2/2