1. Device Name KDS TCXO

2. Model Name DSB321SCL

3. Nominal Frequency 26.000 MHz

4. Mass 0.03g max.

5. Absolute Maximum Ratings

	Item	Symbol	Rating	Unit
1	Supply Voltage	V_{CC}	-0.3 ~ +6.0	V
2	Storage Temperature Range	$T_{_STG}$	-40 ~ +85	°C

6. Recommended Operating Conditions

	Item	Symbol	min.	typ.	max.	Unit
1	Supply Voltage	V_{CC}	+3.00	+3.3	+3.60	V
2	Load Impedance (resistance part)	L_{oad}_R	9	10	11	kΩ
	(parallel capacitance)	L_{oad}_C	9	10	11	pF
3	Operable Temperature Range	$T_{_OPR}$	-40	-	+85	°C

7. Electrical Characteristics

(T_A =-40 ~ +85 °C, L_{oad}_R//C =10kΩ//10pF, V_{CC}=+3.3V, unless otherwise noted)


	Item	Conditions	Limits			unit	Notes
			min.	Typ	max.		
1	Current Consumption		-	-	1.5	mA	
2	Output Level		0.8	-	-	V_{p-p}	1
3	Symmetry	GND level(DC cut)	40/60	-	60/40	%	
4	Frequency Stability 1.Tolerance	After 2 times reflow Ref. to Nominal Frequency	-	-	±1.5	ppm	2
	2.vs Temperature	T_A =-40 ~ +85 °C Ref. to Frequency(T_A=+25°C)	-	-	±2.5	ppm	
	3.vs Supply Voltage	V_{CC}=+3.3V±5%	-	-	±0.2	ppm	
	4.vs Load Variation	L_{oad}_R//C =(10kΩ//10pF)±10%	-	-	±0.2	ppm	
	5.vs Aging	T_A= Room ambient	-	-	±1.0	ppm/year	
5	Start Up	@90% of final Vout level	-	-	2.0	ms	
6	Phase Noise	Relative to F0 level offset 1kHz	-	-	-135	dBc/Hz	

Notes

1. Clipped sine wave (DC-coupled)
2. Please leave after reflow in 2h or more at room ambient.

8. Outline, Pin Connections

Outline




Pin Connections

Pin No.	Connection
#1	GND
#2	GND
#3	Output
#4	Vcc

Marking
(1) Frequency 26.00 (MHz, 4digits)
(2) Model code Z
(3) EIA Date code Year (1digit) + Week (2digits)
e.g. 2009/1/1 → 901

unit: mm
Dimensional Tolerance: ±0.15

9. Measurement Circuit



L_{oad}_R=10kΩ
L_{oad}_C=10pF (Include Jig stray capacitance)

TITLE	Remark		
TCXO SPECIFICATION			
Date	Spec. No.	Rev.	Page
2009/09/02	ZC04566	-	2/2